







#### Available Packaging

G	AP	30G	55G

# The Juggernaut Difference

Juggernaut The Ultimate Cold Water Floor Stripper is designed specifically to remove finish and sealer from heavily burnished floors in one application! When your burnished resilient tile, concrete, or masonry floors require a strip out, Juggernaut is the solution! Juggernaut is powerful without butyl, works in one application, and dilutes at 1:10 for less burnished finishes and 1:4 for tough jobs.

**Juggernaut** is designed to be used on all hard floor surfaces. Juggernaut has a mild and pleasant fragrance.

## **FEATURES**

- Faster acting
- Faster penetrating
- Liquefies heavily burnished finish and sealer
- Contains Liquescent® technology for better performance and safety
- Butyl-free
- No added fragrance
- Less labor intensive
- Works in cold water
- Resists clogging of pads







## **DIRECTIONS FOR USE**

(for use in COLD water)

#### To Remove Non-Burnished Floor Finishes:

Use 12 oz./gallon water (100 ml/l), (1:10).

- Apply Juggernaut solution liberally. Allow to stand 15–25 minutes on the floor depending on the number of coats needed to be removed..
- 2. Machine scrub.
- 3. Pick up solution. Do not allow to dry on floor.
- 4. Rinse floor at least twice with cold water.
- 5. After floor is dry apply finish.

#### To Remove Burnished Floor Finishes or Sealers:

Use 32 oz./gallon water (250 ml/l), (1:4).

Apply Juggernaut solution liberally. Allow to stand 20–30
minutes in the floor depending on the number of coats
needed to be removed.

TECHNICAL SPECIFICATIONS			
Total Actives	38.0 ± 0.2%		
pH Concentrate	13.0 ± 0.2		
pH (1:4)	12.3 ± 0.2		
Weight/Gallon	8.76 lbs		
Flash Point	None to Boiling		
Color	Purple		
Fragrance	Mild/Sweet		
Hard Water Stability (1:10 with 350 ppm hard water)	Clear		
Rinsing Properties	Excellent		
Freeze-Thaw Stability	Unaffected by Freezing		
Foaming Properties	Extremely Low		

# Recommended for use with Buckeye's Action Control System® II.

For stripping non-burnished finish, use the GREEN Action Lock II Connector™.



For stripping burnished finish or seal, use the GRAY Action Lock II Connector.



Product produced under one or more of the following U.S. patents: 5,080,822; 5,080,831; 5,158,710; 5,419,848; 5,585,341 and 5,849,682. Canadian patents: 2,056,425; 2,080,352 and 2,057,027.

For more information about Juggernaut, scan this code.

