


METAL INTERLOCK/NO BUFF FLOOR FINISH



Available Packaging



The Clarion Difference

Clarion Metal Interlock/No Buff Floor Finish maintains its high gloss with minimal maintenance. **Clarion** is an extremely durable floor finish that is ideal when there is limited equipment or manpower for a buffing program. **Clarion** is versatile and may be used on all porous floors.



FEATURES

Easy to Apply

- High gloss
- Self-Leveling Coats apply easily
- Dries rapidly Reduces labor costs

Highly Durable

- Non-Powdering Finish stays intact to last longer
- Non-Yellowing Extends stripping intervals, reducing labor cost
- Holds up under extreme conditions

Minimal Maintenance

- No buffing required
- Detergent resistant Holds up to repeated moppings
- Resists scuffs Floors look better longer

Versatile

- Resilient floors Vinyl, rubber, asphalt, vinyl composition tile
- Hard floors Terrazzo, slate, marble, concrete, quarry tile
- Ideal for grocery stores, classrooms, and more





DIRECTIONS FOR USE

FLOOR PREPARATION:

- 1. Strip floor using Buckeye **RipSaw**™ or other Buckeye stripper.
- 2. After picking up solution, rinse floor until no residue remains.
- 3. Allow floor to dry before applying **Clarion**.

APPLICATION:

- 1. Use a clean mop and bucket.
- 2. Saturate mop, press firmly into wringer to remove excess finish. Do not wring mop.
- 3. Apply Clarion in even coats.
- 4. Allow each coat to dry, usually 20 to 30 minutes under normal humidity conditions.
- 5. Apply seven coats to achieve maximum gloss and durability. Apply four coats maximum per 24-hour period.

MAINTENANCE:

- 1. Dust mop floor.
- 2. Damp mop as needed, using Buckeye **True 7**™.

TECHNICAL SPECIFICATIONS	
рН	8.2 – 8.6
Leveling	Excellent
Freeze/Thaw Stability	Passes 3 cycles
Removability	Excellent
Drying Time	20–30 minutes
Black Mark Resistance	Excellent
Film Color	Water-Clear
Scrubability	Excellent
Weight/Gallon	8.56 lbs
Slip Resistance	U.L. Classified



For more information about Clarion, scan this code.

