


Buckeye®

VERDE —ULTRA

ENVIRONMENTAL FLOOR FINISH



Available Packaging



The Verde Ultra Difference

When you want the greatest response to burnishing, **Verde Ultra** Floor Finish quickly builds to a radiant gloss. Each time you burnish **Verde Ultra**, you will achieve a more brilliant shine and enhanced durability. Designed for green floor care programs, **Verde Ultra** also meets the most stringent environmental standards without sacrificing product performance.



DIRECTIONS FOR USE

FLOOR PREPARATION:

1. Strip floor using Buckeye **Penetrate™**, Buckeye's Green Seal® certified floor stripper.
2. After picking up solution, rinse floor until no residue remains.
3. Allow floor to dry before applying **Verde Ultra**.

APPLICATION:

1. Use a clean mop and bucket.
2. Saturate mop, press firmly into wringer to remove excess finish. Do not wring mop.
3. Apply finish in even coats.
4. Allow each coat to dry, usually 20 to 30 minutes.
5. Apply multiple coats until desired gloss is achieved.

MAINTENANCE:

1. Dust mop floor.
2. Damp mop floor as needed, using Buckeye **Tenacity®**, **True 7™**, or other Buckeye cleaner.
3. Burnish as needed.

Note: Ensure adequate ventilation, especially in confined areas.

FEATURES

- Superior response to burnishing
- Zinc-free
- High gloss
- Green Seal™ certified
- Non-yellowing
- Non-powdering
- Ammonia-free
- U.L. listed
- Easy to repair and maintain

TECHNICAL SPECIFICATIONS

pH	7.6 ± 0.2
Leveling	Excellent
Freeze/Thaw Stability	Pass Three Cycles
Removability	Excellent
Drying Time	20–30 minutes
Black Mark Resistance	Very Good
Film Color	Clear
Weight/Gallon	8.55 lbs
Slip Resistance	UL Classified

For more information about Verde Ultra, scan this code.



BUCKEYE INTERNATIONAL, INC.

2700 WAGNER PLACE • MARYLAND HEIGHTS • MO 63043 • USA • 800.321.2583

www.buckeyeinternational.com

2565 (6/25)

FLOOR CARE